

## **Bike Build Specs**

CALL 860-537-4306 or E-mail techinfo@avalanchedownhillracing.com us for more details and help

## LET AVALANCHE SUSPENSION HELP CREATE YOUR BUILD

All data is our best estimate based on the information provided online



## **2020 SUR-RON Light Bee X**

MODEL VERSION YEARS	
FRAME MATERIAL	STEEL
SHOCK SIZE	10.5 x 3.50
TRAVEL MM	210
UPPER REDUCER	23.8 x 8.0
LOWER REDUCER	23.8 x 8.0
LINKAGE	ROCKER LINKAGE (RISING RATE)

AVERAGE LEVERAGE	2.36
STARTING LEVERAGE	3.1
SAG POINT LEVERAGE	2.7
ENDING LEVERAGE	2.2
PROGRESSION %	29.0
LEVERAGE CURVE	HPL High Progressive Linear
SHOCK TUNE	PROGRESSIVE HPL
OEM SHOCK	DNM Burner-RCP 2S
OEM SHOCK	KKE
UPGRADE OPTION	BOMBER CR
UPGRADE OPTION	AVALANCHE WOODIE
UPGRADE OPTION	FOX VANRC
SUGGESTED SHOCK SPRING (140/160/180/200/220/240 LBS)	400,400,450,450,500,550,
HEAD TUBE ANGLE	64
<b>RECOMMENDED FORK TRAVEL</b>	203
SUGGESTED FORK SPRING WITH OUR CARTRIDGE(140/160/180/200/220/240 LBS)	50,50,55,60,65,65,
COMMENTS	ESTIMATED LEVERAGE
COMMENTS	240 x 87 stock shock, KKE SHOCK SPRING 450 X 192 LG X 36 MM ID ENDS 38.5 MIDDLE, USE CANE CREEK ADAP